

ECOBULK MX



The **ECOBULK MX 1000** with discharge opening **DN 150** is the perfect solution for viscous products and pastes.

ECOBULK IBCs are specially designed for reconditioning. The plastic and metal components of the modular system are easy to replace. ECOBULK IBCs combine high economic efficiency and a turn-key approach to environmental protection.

1,9 maximum density

CERTIFICATIONS

FDA

with 1000 litre pallet max. density 1,2
with 1200 litre pallet max. density 1,4
with 1500 litre pallet max. density 1,0

CAPACITY

MX 1000 liter (270 gal)

MATERIAL

Inside container: made of corrosion-free recycled HDPE.
SMP receptacle for an optional outside container: welded and galvanized double steel grid.
Base: made of steel (see), shaped for high stability and complete matchings of the inside container.

PALLETS

4 way entry
see

1200

1500



FILLING OPENING

DN 150 with screw cap
DN 200 with screw cap
DN 800 with clamping cap

DISCHARGE OPENING

Discharge opening DN 150 sealed by
also-lined PE-tub, closed by o-ring,
PE disc and screw cap.
Accessory for foamy water: DN 150.

MEASUREMENTS

MX 1000 LxWxH: 1200x1000x1160

WEIGHT

MX 1000: 60 kg with 4-tines pallet
MX 1000: 60 kg with 1200mm pallet
MX 1000: 90 kg with 1500mm pallet